

Fibered Aluminum Roof Coating

Energy Saving Aluminum Sealant

- Reduces Heat Build Up & Keeps Building Interiors Cooler
- Specially Developed to Provide Longer Life
- Protects Roof Surfaces
- Provides a Highly Reflective Surface
- Meets ASTM D 1227, Type III



Revised: 07/10

Manufacturer

ThorWorks Industries
2520 S. Campbell St.
Sandusky, Ohio
Phone: 800-326-1994
Fax: 419-626-5477
www.sealmaster.net

Description

This premium energy saving formula stays brighter longer. It will seal, protect, and reflect solar heat using a proven blend of selected waterproofing pigments. Forms an excellent adhesive bond with most substrates. Areas immediately under roof will remain approximately 15-20 degrees cooler in summer. In winter, heat is reflected back into the building, saving energy costs. Dries bright silver.



Uses

- Metal & Concrete Roofs
- Weathered Asphalt
- Metal Buildings/Grain Bins
- Built-Up Roofs & Mobile Homes
- Mod. Bitumen, SBS & APP

Surface Preparation

Repair all cracks, splits, and holes using SealMaster All Weather Roof Cement and Asphalt Coated Reinforcing Fabric, adhering to the directions on their label. Allow repairs to weather at least 30 days before coating. Clean surfaces thoroughly by brooming away dirt, dust and loose particulate. Remove all grease and oil using detergent and water, rinsing thoroughly. Broom away excess water and allow to dry completely.

Application

Mix coating thoroughly before and during application. Uniformly coat the entire surface with the coating using a roofing brush or roller. Do not apply to wet or damp surfaces. Do not apply to roofs which hold water. Standing water will result in premature failure.

Drying Time

Allow 24 hours depending on weather conditions.

Clean Up

Clean up with waterless hand cleaner immediately after use.

Coverage (Approximate)

- Metal Roofs: 75-100 sq. ft. per gallon
- Composition Roofs: 50-75 sq. ft. per gallon

Fibered Aluminum Roof Coating
Energy Saving Aluminum Sealant

Form No.: F2060P

Precautions

- Do Not Heat or Thin
- Do Not Store at Temperatures Above 100°F
- Combustible. Contains Petroleum Distillate

Safety And Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 500 gm/liter max
- Use With Adequate Ventilation
- KEEP OUT OF REACH OF CHILDREN

Packaging

Item #	Container Size	Pack	Weight	Price
F2060P	4.75 Gallon Pail	1	49 lbs.	\$ 67.99

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Asphalt	8052-42-4
Stoddard Solvent	64742-88-7
Aluminum Flake	7429-90-5
Cellulose	9004-34-6
Calcium Carbonate	1317-65-3