

Fibered Emulsion Roof and Foundation Coating

Fibered Asphalt Emulsion Coating

- Easy To Apply
- Soap & Water Cleanup
- Zero Voc Formula
- Seals Out Water & Moisture
- Environmentally Friendly Water-Based Formula
- Meets ASTM D 1277, Type IV



Revised: 07/10

Manufacturer

ThorWorks Industries
2520 S. Campbell St.
Sandusky, Ohio
Phone: 800-326-1994
Fax: 419-626-5477
www.sealmaster.net

Description

A fiberized asphalt emulsion designed for coating a variety of roof surfaces and concrete foundations. Dries black.

Uses

- Metal Roofs, Concrete Roofs, Built - Up Roofs, Wood Roofs, Roof Felts, and Concrete Foundations

Surface Preparation

When coating roofs, nail down any loose laps or parts. Repair splits, cracks, weak or leaking areas with SealMaster All Weather Roof Cement and Asphalt Coated Reinforcing Fabric, adhering to the directions on the container. Brush or broom away all dust, dirt, loose gravel or debris. Remove grease or oil with a detergent and water making sure to thoroughly rinse. Broom away any standing water.

Application

Stir before and during use. Coat the entire surface using a brush or roller. Best results are obtained if two coats are applied with the second coat applied perpendicular to the first. Allow a minimum of 36 hours between coats. Foundation walls should be thoroughly broomed and rinsed with clean water, ensuring the removal of dirt, dust and loose concrete particles. Apply SealMaster Fibered Emulsion Roof and Foundation Coating with a brush or roller. To reinforce cracks, sandwich a layer of SealMaster Asphalt Coated Reinforcing Fabric between subsequent coats. Allow a minimum of 36 hours curing prior to backfilling.

Drying Time

Allow 24 hours depending on weather conditions.

Clean Up

- While wet, use soap and water.
- When dry, use waterless hand cleaner.

Weather Conditions

- Application temperature must be a minimum of 60°F and rising. Do not apply when temperature is expected to drop below 50°F within a 24-hour period.



Fibered Emulsion Roof and Foundation Coating
Fibered Asphalt Emulsion Coating

Form No.: F2050P

Weather Conditions (Ctd.)

- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

- Metal Surfaces: 75-100 sq. ft. per gallon
- Concrete and Masonry Surfaces: 50-75 sq. ft. per gallon
- Composition Roofing: 50-75 sq. ft. per gallon

Precautions

- Do Not Heat or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50°F

Safety And Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 0 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

Packaging

Item #	Container Size	Pack	Weight	Price
F2050D	55 Gallon Drum	1	513 lbs.	\$617.99
F2050P	4.75 Gallon Pail	1	46 lbs.	\$ 59.99
F2050G	.9 Gallon Pail	6	55 lbs.	\$ 14.99

*At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Clay	1332-58-7
Water	7732-18-5
Synthetic Fibers	Proprietary
Potassium Bichromate	7778-50-9