

Fibered Roof and Foundation Coating

Asphalt Based Coating

- Protects Built-Up Composition, Metal, Gravel & Concrete Roofs & Foundations
- Use For Coating Entire Surface Area, Above Or Below Grade
- Meets ASTM D 4479



Manufacturer:

ThorWorks Industries
2520 S. Campbell St.
Sandusky, Ohio
Phone: 800-326-1994
Fax: 419-626-5477
www.sealmaster.net

Description

A mixture of liquid asphalt and fibers which forms a tough, adhesive bond with most roof surfaces. Highly resistant to water and other types of weather damage. Seals small cracks, joints, seams and nail holes. Dries black.

Uses

- Metal, Concrete, Wood, and Built - Up Roofs, Roof Felts, Concrete Foundations



Surface Preparation

For best results, clean surface with brush or broom, removing all loose sediment and dirt. Nail down any loose parts. Repair any leaking or weak areas with SealMaster All Weather Roof Cement and SealMaster Asphalt Coated Reinforcing Fabric repair material.

Application

Stir before and during use. Coat entire surface area with SealMaster Fibered Roof And Foundation Coating. For best results, apply a uniform coating with roofing brush when surface is dry. One coat provides year round protection.

Drying Time

Allow 24 hours depending on weather conditions.

Clean Up

Clean tools with mineral spirits or kerosene in a well ventilated area immediately after use.

Coverage (Approximate)

- Metal Roofing: 60-70 sq. ft. per gallon
- Felt or Composition: 50-60 sq. ft. per gallon
- Concrete or Masonry Surfaces: 25-50 sq. ft. per gallon
- Strip Composition or Dried Out Roofing: 25-50 sq. ft. per gallon

Precautions

- Do Not Heat or Thin
- Do Not Store at Temperatures Above 100°F
- Do Not Apply Over Coal Tar Surfaces
- Do Not Apply Where Hydrostatic Pressures Could Be Encountered
- Combustible. Contains Petroleum Distillate

Fibered Roof and Foundation Coating
Asphalt Based Coating

Safety And Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 250 gm/liter max
- Use With Adequate Ventilation
- KEEP OUT OF REACH OF CHILDREN

Packaging

Item #	Container Size	Pack	Weight	Price
F2025P	4.75 Gallon Pail	1	44 lbs.	\$ 44.12
F2025G	.9 Gallon Pail	6	52 lbs.	\$ 14.99

*At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Mineral Spirits	64742-88-7
Calcium Carbonate	1317-65-3
Cellulose Fibers	9004-34-6
Magnesium Carbonate	546-93-0