

# Flashing Cement

## Professional Grade Flashing and Repair Product

- Long-Lasting Protection
- All-Weather Formula
- Will Not Run or Sag
- Added Flexibility & Elasticity
- Superior Flashing, Patching & Leak Repair Cement
- Meets ASTM D 4586 Type 1 & ASTM D 3409



Revised: 07/10

### Manufacturer

ThorWorks Industries  
2520 S. Campbell St.  
Sandusky, Ohio  
Phone: 800-326-1994  
Fax: 419-626-5477  
www.sealmaster.net

### Description

A professional grade flashing and repair product that cures to a tough, protective barrier. Its non-sag property and exceptional adhesion makes this an ideal cement for the construction and repair of all flashings, metal joints, seams, coping, vent pipes, skylights and chimneys. This cold applied cement is ideally suited for sealing cracks, holes and tears in built-up roofs and modified bitumen. Dries Black.

### Uses

- Splits & Seams
- Vents
- Metal Joints
- Coping
- Flashings
- Skylights
- Chimneys



### Surface Preparation

All surfaces to be treated must be free from oil, grease and other foreign materials prior to application. The surface must be firm and free from loose material. On composition roofs, open any breaks or blisters to be patched and permit to dry out before applying this product.

### Application

**Pails:** Trowel Grade Material. Allow at least 24 hours to dry (70°F and less than 50% humidity with no rain) before applying a surface coating. Use above or below grade.

**Tubes:** Trim Nozzle to desired bead size. Puncture foil at innerbase of nozzle. Using a caulking gun, apply to a minimum wet thickness of 1/4". Allow at least 24 hours to dry (70°F and less than 50% humidity with no rain) before applying a surface coating.

### Drying Time

Dries to the touch in 8-24 hours, depending on weather conditions.

### Clean Up

Clean up with waterless hand cleaner immediately after use.

### Coverage (Approximate)

- Approximately 12 square feet per gallon.
- One 10 ounce tube will fill approximately 30 lineal feet at 1/4" thick.

### Precautions

- Do Not Heat or Thin
- Do Not Store Container at Temperatures Above 100°F
- Combustible. Contains Petroleum Distillate

Flashing Cement  
Professional Grade Flashing and Repair Product

Form No.: F2010P

## Safety And Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 300 Gm/Liter Max
- Use With Adequate Ventilation
- Keep Out of Reach of Children

## Packaging

Item #	Container Size	Pack	Weight	Price
F2010P	4.75 Gallon Pail	1	50 lbs.	\$ 37.99
F2010G	.9 Gallon Pail	6	56 lbs.	\$ 10.99

\*At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Calcium Carbonate	1317-65-3
Mineral Spirits	64742-88-7
Cellulose Fibers	9004-34-6
Attapulgate Clay	12174-11-7