

White Resin Treated Glass Fabric

Superior Reinforcing Material

- Ideal for Use With White Patch Materials & Coatings
- Reinforces Patchwork for Maximum Durability
- White Colored Fabric



Revised: 01/09

Manufacturer:

ThorWorks Industries
2520 S. Campbell St.
Sandusky, Ohio
Phone: 800-326-1994
Fax: 419-626-5477
www.SealMaster.net

Description

Reinforcing fabric for patching holes and cracks 1/4 inch wide or more.

Uses

- Cracks, Seams, Flashings, Blisters & Gutters

Surface Preparation

For best results, clean area of loose dirt and debris. If moisture is present allow area to dry.

Application

Apply SealMaster White Elastomeric Roof Patch to defective area. Extend the patch 3" beyond the area to be repaired. Spot stick roof repair glass in position over area. Press into place. Coat fabric with roof patch so that fabric is sandwiched between two layers of material.

Coverage (Approximate)

- 4 inches wide X 50 feet long.

Safety And Environmental Precautions

- Refer to Material Safety Data Sheet before using.
- For Exterior Application Only.
- Environmental information is on the Material Safety Data Sheet.
- KEEP OUT OF REACH OF CHILDREN.



White Resin Treated Glass Fabric
Superior Reinforcing Material

Form No.: F2075

Packaging

Item #	Container Size	Pack	Weight
F2075	6" X 50' Roll	24	10 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.